



SILENCED DIESEL SE4000DL



SE4000DL 4.0kVA "SILENCED" RANGE
PORTABLE DIESEL GENERATOR
STANDARD FEATURES

- Recoil start Lombardini engine with direct injection
- Acoustic housing
- 25mm tubular steel frame and high efficiency silencer
- Heavy duty brushless maintenance free alternator with smooth wave format
- Dual voltage output with overload protection
- Twin folding carry handles

General Specifications

Range	Silenced
Frequency(Hz)	50
Max.Power (kVA)	4.0
Max.Power (kW)	3.2
Nominal Voltage	230 / 115
Number of phase	Single Phase
Acoustic pressure level Lw(A)	96
Noise Level dB(A) -7m	71

Engine Specifications

Engine trademark	Lombardini
Engine Type	15LD 350S
Distribution	O.H.V
Start	Recoil
Fuel	Diesel
Autonomy (h) @ 75% load	13.0
Consumption (L/h) @ 75%load	1.0
Tank (L)	13.0
Low Oil Pressure Shutdown	Yes
Capacity (cm3)	349
Oil Capacity (L)	1.2

Alternator Specifications

Manufacturer	NSM
Model	K100F
Type	Heavy Duty Brushless Maintenance Free
Regulation	Mechanical
Protection Class	IP23
Insulation Class	H

Control Panel & Sockets

Type	Metal
Sockets	1 x 16a & 1 x 32a 115v 1 x 16a 230v
Voltage Selector Switch	Yes
Individual Socket Protection	Push button MCB

Dimensions & Weight

Length (mm)	775
Width (mm)	475
Height (mm)	560
Dry Weight (kg)	96

Options

Single Voltage
LUL Approved Version/ Rail Track Specification
115v CTE
Trolley kit